


ALL TERRAIN LIFTING SOLUTIONS





> APPLICATION

The Dirker Crane-Lift is designed to reach up to 3 m and lift up to 6 m. With Nose end attachments designed to specific application requirements. The Dirker Crane-Lift can be adapted and be used in Saharan to Siberian conditions, in industries such as:

Agricultural Forestry & Sawmills Construction

Mining

Defence Forces

Contact us for more information regarding the applications of the Dirker Crane-Lift

> EVOLUTION

The Dirker Crane-Lift is a perfect example of the evolution team in action. We are still ready to evolve even more to implement your ideas and requirements.

Due to the Dirker Evolution design and manufacturing's teams ability to create solutions, as well as the ability to take any idea from concept to final product extremely

+27 (0) 12 942 1446 | sales@dirkermachines.com www.dirkermachines.com | Pretoria, South Africa



CRANE-LIFT SPEC SHEET

| ENGINE | | DRIVE PUMP | |
|---------------------|--|--------------------|-------------------------|
| Make | Deutz F4L912 | Model | PMP 50x50 |
| Power | 49Kw/230nm @ 1600rpm | Operator Control | Servo Foot Pedal |
| RPM | Governed @ 2300rpm | Displacement | 45cc Per Side |
| Mounting | 6 Point Rubber Mount | Relief Valve | 280 Bar |
| Safety | Mechanical Shut Off | Hot Oil Shuttle | Pump Internal |
| HYDRAULIC & | FUEL TANK | WHEELS | |
| Hyd Tank Type | Framing Tubing Integrated | Front Tyres | 17.5x25 |
| Hyd Tank Capacity | 145L (170 for System) | Front Rim | 17.5" Three Piece |
| Fuel Tank Type | Bolt Mounted on Frame | Rear Tyres | 400/60x15.5 |
| Fuel Tank Capacity | 85L | Rear Rim | 15.5 One Piece |
| BRAKES | | OPERATING I | MASS |
| Park Brake | Muli Disc Spring Applied | Front Unladen | 2100KG |
| Park Brake Release | 18 Bar Hydraulic Pressure | Rear Unladen | 1850KG |
| Park Brake Valve | Mechanical | Total Unladen | 4560KG |
| Service Brake | Hydrostatic Foot Pedal Control | Lifting Capacity | Up To 3000KG |
| CABIN | | ATTACHMEN | IT |
| Туре | Frame Integrated | Type | Brick Grab |
| Optional Protection | Guarded Sided Doors | Rotator | 5 Ton Rotator |
| | Front Top Guard | AUX HYDRAU | ILIC SYSTEM |
| | Front Bottom Guard | | |
| Seat Belt | Suspended Lap Belt | Pump | 28cc Gear Pump |
| HVAC Cabin | Optional | Operating Pressure | 170 Bar |
| Туре | Sealed Frame Integrated | Oil Cooler | Electric Fan Cooled |
| HVAC System | 12v Fan, Engine Belt Drive Aircon Compressor | Control Valves | 1 x Double Left Hand |
| Windows | Glazed With Wiper | | 1 x Double Right Hand |
| WHEEL DRIV | E SYSTEM | | |
| Drive Motor | Poclain MS18 2800cc | Wheel RPM | 32rpm @ 2300 Engine RPM |
| Wheel Torque | 13300nm Per Wheel | | |

